

ADVAN



All New Ultimate Street Sport Tire

ADVAN A052



SPEED RANGE (Y)/Y/W/V

HighPerformance /Sports Car

18 inch 17 inch 16 inch

Dry High Grip High Speed Handling Asymmetric

Pattern No. A052

Asymmetric tread pattern

Adopting Mound-Profile

For controlling the contact pressure of each block.

Balancing wet performance with the stability in the high speed area.

Two Straight Grooves

By locating 2 main straight grooves in the inside.

Enhance straight-line stability. And superior anti-hydroplaning.



High-rigidity Tread Rib

Locating 2 main grooves at inside, we realize the expansion of the contact area of the outside.

Delivering powerful cornering capability.

Straight Thin Groove

Locating a straight thin groove in the outside part where receive big pressure in the corner.

Enhance efficiently dissipate heat. Preventing time-drop.

All new Sport Compound, Specially Developed for A052

Extreme Grip
(Dry&Wet)



Fuel Efficiency

MS Technology
Ultra High level combination of each technology.

BluEarth Technology

Positioning Map & Target User

Sport Performance

High Grip / Circuit / Lap Time



ADVAN A050
(M/MH/H)



ADVAN A050 has several compounds which are fitted running distance or temperature range. We recommend A050 to the user who want to win the race seriously.

ADVAN A052



ADVAN A052 keeps both high driving performance and environmental performance at a high level. The handling performance is excellent. As well as a Pro-driver, it is suitable for all people who want to enjoy motor sports. Compared with ADVAN NEOVA AD08R, we recommend ADVAN A050 to more circuit-oriented user.

ADVAN NEOVA AD09



ADVAN AD09 is a street sport tire with aggressive pattern design. This is an almighty performance tire corresponding from street to circuit. Compared with ADVAN A052, we recommend ADVAN NEOVA AD09 to more street-oriented user.

Sport Performance

High Grip / Circuit / Lap Time



< Sport Performance >
A052 is higher product of NEOVA and lower product of A050.

ADVAN A052

Pattern No. A052

| Inch | Series | Dimensions | RF/XL | Overall Diameter (mm) | Approved Rim Width (inch) |
|---------------|---------------|----------------|-------|-----------------------|---------------------------|
| 18 | 30 | 295/30R18 98Y | XL | 635 | 10-11 |
| | | 315/30R18 98Y | | 647 | 10.5-11.5 |
| | 35 | 255/35R18 94Y | XL | 635 | 8.5-10 |
| | | 265/35R18 97Y | | 643 | 9-10.5 |
| | 40 | 295/35R18 103Y | XL | 663 | 10-11.5 |
| | | 225/40R18 92Y | XL | 637 | 7.5-9 |
| 235/40R18 95Y | | XL | 645 | 8-9.5 | |
| 245/40R18 97Y | | XL | 653 | 8-9.5 | |
| 17 | 40 | 255/40R18 99Y | XL | 661 | 8.5-10 |
| | | 265/40R18 101Y | XL | 669 | 9-10.5 |
| | 45 | 255/40R17 98W | XL | 636 | 8.5-10 |
| | | 205/45R17 88W | XL | 616 | 6.5-7.5 |
| | | 215/45R17 91W | XL | 626 | 7-8 |
| | | 225/45R17 94W | XL | 634 | 7-8.5 |
| 16 | 45 | 235/45R17 97W | XL | 644 | 7.5-9 |
| | | 225/45R16 93W | XL | 608 | 7-8.5 |
| | 50 | 205/50R16 91W | XL | 612 | 5.5-7.5 |
| | | 225/50R16 96W | XL | 632 | 6-8 |
| 55 | 205/55R16 94W | XL | 632 | 5.5-7.5 | |

XL = Extra Load